

## DE 06-12 Power adaptor 12V / 0.5A

Power adaptor with a 1.1 m flexible cable terminated by a plug is intended for powering Jablotron devices like wireless keyboards, GSM communicators or UC receivers etc. The compact dimensions of the case allow installation into a standard electro-installation junction box for hidden installation beneath Jablotron wall-box-mounted products such as the above-mentioned items. The screw holes for M3 screws are also useful for installation in typical junction boxes where fixing is required.



**Installation shall always be provided by a qualified electrician.**

### Technical specifications

Supply voltage	100 ~ 240 V AC, class protection II
Output voltage	12V DC ( $\pm 2\%$ )
Output current	500 mA
Peak output current T<5 min	1000 mA
Output power	12 W max.
Short-circuit protection and overload protection	yes
Enclosure protection	IP64
Dimensions	50 x 48 x 25 mm
Input cable	length 110 mm (230 V), diameter 1.3 mm (AWG 16)
Operational conditions according to	EN 50131-1 II. Environmental class
Working temperature range	-10 °C to +40 °C
Complies with	EN 50130-4, EN 55022, EN 60950-1



JABLOTRON ALARMS a.s. hereby declares that the DE06-12 is in a compliance with the relevant Union harmonisation legislation: Directives No: 2014/35/EU, 2014/30/EU, 2011/65/EU. The original of the conformity assessment can be found at [www.jablotron.com](http://www.jablotron.com) - Section Downloads.



**Note:** Although this product does not contain any harmful materials we suggest you return the product to the dealer or directly to the producer after use.

**JABLOTRON**  
CREATING ALARMS

JABLOTRON ALARMS a.s.  
Pod Skalkou 4567/33  
46601 Jablonec nad Nisou  
Czech Republic  
Tel.: +420 483 559 911  
Fax: +420 483 559 993  
Internet: [www.jablotron.com](http://www.jablotron.com)