



JI-114Z Ethernet switch PoE - 4 Ports

The PoE switch is suitable for the easy and fast extension of your local LAN. It is equipped with four powerful PoE ports for data connection and to power supply JABLOTRON IP cameras using one cable.

Description

The PoE switch supports networks at both 10 Mbps and 100 Mbps.

Caractéristiques techniques

Power Input	51 V DC
Max. current	1.25 A
Interfaces	5x RJ-45 10/100 Mbps Ethernet
PoE ports	4
Highest priority port	1 (first port)
Max. port output	30 W
Max. total output	58 W
PoE standard	IEEE 802.3af, IEEE 802.3at
Max. length of cable CAT-5e with PoE:	
EXTEND OFF function (10/100 Mbps)	150 m
EXTEND ON function (10 Mbps)	250 m
Transmission speed	Ethernet: 10 Mbps (Half Duplex)/20 Mbps (Full Duplex) Fast Ethernet: 100 Mbps (Half Duplex)/200 Mbps (Full Duplex)
Supported transmission medium	Ethernet: cat. 3 or higher, UTP/STP Fast Ethernet: cat. 5 or higher, UTP/STP
Max. transmission capacity	1 Gbps
Humidity	10 % to 90 %, non-condensing

Operational temperatures	0 °C to +40 °C
Storage temperatures	-40 °C to +70 °C
Protection class	IP20
Dimensions, weight	132 x 28 x 94 mm, 300 g
Complies with	EN 55032:2015, EN 50130-4:2011+A1:2014, EN 61000-3-2:2014. EN 61000-3-3:2013