

DHI-LM49-S400

49" UHD Monitor



Features:

- 4K Ultra-HD resolution
- Using tamper-proof metal housing
- Slim 8mm narrow bezel design
- Built-in 3D COMB filter and 3D Noise Reduction
- 8ms response time for no motion blur, judder or ghosting
- 1.07B colors, for a realistic and immersive visual experience
- High fidelity digital processing for a brilliant and vivid video
- 178°/178° wide uninterupted viewing angle
- Professional thermal design to extend equipment lifespan
- Built-in power, low energy consumption, ultra-quiet
- Support multiple signals, such as HDMI, DP, VGA, USB multimedia, Audio, RS232



Technical Specification

Model

Model	DHI-LM49-S400
-------	---------------

Display

Screen Size	49"
Aspect Ratio	16:9
Resolution	3840×2160 (UHD)
Backlight	LED
Brightness/Luminance	450cd/㎡
Contrast	4700:1
Display Color	1.07B(10bit)
Viewing Angle(H/V)	178°(H)/178°(V)
Response Time	8ms
Refresh Rate	60Hz

Signals

Input	DP 1.2a×1, HDMI 2.0×2, VGA(D-Sub)×1, USB multimedia×1, Audio×1, RJ45(RS232)×1	
Output	RJ45(RS232)×1	
	Speaker	5W×2

General

Power Supply	AC100~240V (+/-10%), 50/60 Hz
--------------	-------------------------------

Consumption (Standard)	<145W	
Type	Internal	
Net Weight	20.5kg	
Gross Weight	30.4kg	
Bezel Width	8mm (U/L/R/B)	
Wall Mount	400×400mm (15.7"×15.7")	
Dimension without standard (W×H×D)	1091.5×623.2×65.0mm (43.0"×24.5"×2.6")	
Package(W×H×D)	1275×795×255mm (50.2"×31.3"×10.0")	
Work Environment	Temperature	0°C~40°C (32°F~104°F)
	Humidity	10%~85%

Accessory

Standard	HDMI cable, power cable, hanging bracket, remote control
Optional	Pedestal

Certifications

Certifications	CE/FCC
----------------	--------

Dimensions(mm)

